







hi-flow 1L & 2L

CONDENSATE REMOVAL PUMP

Proven reliability and performance. The evolution of this world class tank pump means it's more engineer focused and even easier to install and maintain... when time is precious look no further.



288L/h max. flow



5m max. rec. head (flow rate 10L/h)

KEY FEATURES


- Easy access tank
- Twist & click non return outlet barb
- Built-in spirit level




SUITABILITY


- Up to 384kW / 1.3m Btu/h
- Ducted units; Floor standing & Chassis units; Cassette unit





HI-FLOW 1L & 2L SPECIFICATIONS				
Max. flow	288L/h @ 0 head			
Max. rec. head	5m			
Tank capacity	1L & 2L			
Sound level@1m	55dB(A)			
Power supply	230V AC 50-60Hz 0.6A*			
Rated	Continuously			
Class	I appliance			
Max. output	384kW / 1.3m Btu/h			
Max. water temp	40°C / 104°F			
Inlet/outlet	x3 27mm in, 6-10mm out			
IP Protection	IPX0			
Safety switch	3.0A Normally closed			
Thermal protection	✓			
Fully potted	n/a			
Self priming	n/a			





	HI-FLOW 1L & 2L OPTIONS						
				LITRES PE	ER HOUR		
	0	50	100				30
	1	230V					•
Σ	2					•••	٠.
MET						· · · .	

MEIRE	3					٠	
<u> </u>	2					··.	٠.
	1	230V					•
	0	50	100	150 LITRES PI			300
	HILFLOW 11 & 21 OPTIONS						

5m	max. reco	mmend	ed head	
	٠			
	•	٠		
		٠.		
		· · · ·		
			•.	
150	200	250	300	
TRES PE	ER HOUR			

HI-FLOW 1L & 2L OPTIONS				
Hi-flow 1L	FP2096/2			
Hi-flow 2L	FP2122/2			
* Other voltages available				



SUGGESTED XTRA ACCESSORIES				
Description	Part No.			
Tank pump connector 16mm–21mm	FP2011			
Tube To Soil Stack Adaptor	FP2038			
Vinyl Tube Braided 1/4" (6mm)	AX5110			



For more installation accessories take a look at our Aspen Xtra range

IN THE BOX

Hi-flow 1L or 2L pump • 2m Plug & play power cable • 2 StayClean tablets • Fixing kit • Install manual

Download manual at aspenpumps.com View install video at aspenpumps.com











