



 Nordham is one of the few innovative manufacturers of HVAC/R and Software and Control Products.

The company develops and constructs Systems and precision solutions in domains of Heat-, Refrigeration- and Control- Technologies, as well as Industry Automation.

The main aim of Nordham is maximizing the Development of innovative Products and Sytems, in order to deliver our customers the greatest added value possible.

Headquarter

Nordham Technologies
Frohmestraße 37
D-22457 Hamburg

+49 550 07 230
www.nordham.de
info@nordham.de

in Turkey

Digitech Digital
A.T.B. İş Merkezi G-Blok No: 174
Yenimahalle / Ankara

+90 312 467 5501
www.digitech-ltd.com
iletisim@digitech-ltd.com

www.nordham.de

www.linkedin.com/company/nordham

FM12/16

Condenser Fan Speed Control



FEATURES

- Simple installation and direct installation
- Robust, durable and long lasting box
- Aluminum material
- Compact design
- User friendly interface
- German design and technology
- Long life use

For more information
www.digitech-ltd.com/fm12
www.digitech-ltd.com/fm16

The FM series monophase fan speed control units keep the condenser gas pressure constant by adjusting the fan speed according to the condenser pressure or temperature. In addition to the pressure and temperature sensors, 0-5V, 0-10V or potentiometer can also be connected to provide external control. The soft-start feature softens the fan's first attempt. In cold weather, the fan applies full power for a short period of time at the start of the fan, thus resolving problems such as fan congestion, snow accumulation, etc.

The user-friendly menu allows easy operation without confusion. The desired fan speed can be adjusted in the band frame that the user can adjust.

The FM control units also offer solutions to the needs of monophase motors (suitable for control with phase angle control), heating and dimmers. In addition to temperature, pressure and analogue inputs, other control requirements also provide a

TEKNİK ÖZELLİKLER

Programming	: 4 digit 7 segment LED display and 3 button, EasyGlide® technology
Speed control	: Phase cutting voltage regulation (SCR)
Operating voltage	: 230V AC \pm 10%
Max. Fan amp	: 6A / 9A
Operating frequency	: 50Hz / 60Hz automatic selection
Input type	: Pressure, Temperature, Voltage, RS485 optional
Pressure transmitters	: Ratiometric 5V supply, 0.5-4.5V full scale
Pressure range	: Any pressure range ratiometric sensor can be used
Temperature sensor	: 10K NTC Thermoplastic
Working range	: -40 ° C to + 120 ° C
Voltage control	: 0-5V / 0-10V
Measurement accuracy	: \pm 0.1% 12bit ADC interpolation
Dimensions	: 134mm x 134mm x 84mm
Weight	: 1100gr



FM12



FM16



NORDHAM
TECHNOLOGIES

Nordham Technologies in Turkey

Digitech Digital

A.T.B. İş Merkezi G-Blok No: 174
Yenimahalle / Ankara

+90 312 467 5501
www.digitech-ltd.com
iletisim@digitech-ltd.com